

## Coaxial Cable Connector 21\_BNO-0-4-1/133\_N

### Description

Straight cable jack

Interface standards  
IEC 60169-22



### Technical Data

#### Electrical Data

Impedance not defined  $\Omega$   
Interface frequency max. 0.2 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0161 kg

#### Environmental Data

Operating temperature -50 °C to 125 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	ETFE (Ethylene tetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00008215  
Catalogue drawing DOU-00008217  
Assembly instruction DOC-0000179394

### Ordering Information

Single package 21\_BNO-0-4-1/133\_NE

### Additional Information

Suitable cables RG\_108\_A/U