

Power Splitter

340-3800MHz

- ◆ Wide-band design, cover 340-3800MHz
- ◆ Low PIM
- ◆ Compact size and light weight
- ◆ Easy to be installed
- ◆ Suitable for indoor and outdoor applications
- ◆ Square tube

Orbis product codes:

2 Way 3008483

3 Way 3008484

4 Way 3008485



Technical Data

Electrical Specifications

Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95020133	95030133	95040133
		≤-155	95020135	95030135	95040135
		≤-160	95020137	95030137	95040137
Frequency Range (MHz)			340-3800		
For connecting...antennas			2 Way	3 Way	4 Way
Distribution Loss(dB)			3.0	4.8	6.0
Insertion Loss (dB)			≤0.3	≤0.6	≤0.6
Return Loss (dB)			≥19@340-2700&≥18@3400-3800		
Input Power (W)			≤300		
Peak Power (W)			≤1500		
Impedance (Ω)			50		

Mechanical Specifications

Dimensions,HxWxD(excluding connectors and mounting bracket)(mm)	249x25x25	272.5x25x25	294.9x25x25
Weight (including connectors and mounting bracket) (kg)	0.52	0.58	0.71
Packing Size(mm)	290x85x50(30Pcs/box)	335x85x50(30Pcs/box)	355x85x65(30Pcs/box)
Connector Type	4.3-10 Female(Twisthead)		
Color	Light Gray(Customizable)		
Mounting	Wall Mounted		

Environmental Specifications

Operational Temperature (°C)	-25 to +65
Operational Humidity (%)	≤95
Ingress Protection Class	IP65(Indoor and Outdoor)

Accessories(order separately)

Type No.	Description
30505.0043051	Bracket
50501.0330100	Screw

