



K33

IPAAS Core Alignment




Benefits and Features


- Wide 5.0 inch color LCD monitor with Electrostatic touch screen & bidirectional operation system.
- User friendly GUI.
- Powerful lithium polymer battery with large capacity.
- Lowest Splice Loss.
- Resistance to Shock, Dust and Water
- LED lamp installed on the wind cover for low light condition.

PATENTED

Improved Productivity via Dual Heater




PATENTED



Electrode Life

Up to **10,000** splices

PATENTED



Rotating Blade Life

Up to **75,000** fibers

Specifications

CATEGORY	DESCRIPTION
Fiber alignment	IPAAS Core Alignment
Applicable fibers	SM(G.652), MM(G.651), DS(G.653), NZDS(G.655), SM(G.657 A2/B2), SM(G.657 B3)
Fiber count	Single fiber
Applicable fiber dimensions	Cladding diameter: 80~150μm, Coating diameter: 100μm
Fiber cleave length	7~16mm
Splicing modes	Splice mode: 300, Heat mode: 100
Average splice Loss	SM: 0.02dB, MM: 0.01dB, DS: 0.04dB, NZDS: 0.04dB
Return loss	> 60dB (Typical)
Splicing time	Typical 6 sec. (Quick Mode)
Splice loss estimate	Available
Sleeve heating time	9 sec (IS-45 Sleeve, IS-45 mode), 13 sec (IS-60 Sleeve, IS-60 mode)
Applicable protection sleeve	32mm, 40mm, 60mm (Fiber) / 28mm or 32mm (Connector)
Storage of splice result	The last 10,000 results to be stored in the internal memory. (Image 10,000 results)
Tension test	1.96N ~ 2.25N
Operating conditions	Altitude: 0~5,000m above sea level, Temperature: -10°C~50°C, Humidity: 0~95%, Wind: 15m/s, Non-condensing, Dust proof, Water proof, Shock proof
Storage conditions	Temperature: -40°C~80°C, Humidity: 0~95%
Dimensions	142(W) x 164(L) x 138(H)mm (Including rubber)
Weight	2.25kg (Including battery)
Viewing method and display	Two CMOS cameras and 5.0-inch color LCD monitor with Electrostatic touch screen
Fiber view and magnification	X/Y 200X, Max 400X
Power supply	100~240V
Battery life with heat-shrink	Typical 200 cycles (4700mAh)
Electrode life	Up to 10,000 splices
Terminals	USB

Standard Package

CATEGORY	MODEL	Q'ty
Arc Fusion Splicer	SWIFT K33	1
User guide CD	-	1
Spare electrode	EI-23	1 pair
Cooling Tray	-	1
Transporting Case	Hard Case	1
Battery	4700mAh	1
AC Adapter	-	1
Cleaver	CS-03BT	1
Manual stripper	CF-02	1
Alcohol dispenser	PP	1
Tool box	-	1
USB Cable	-	1

Optional Package

CATEGORY	MODEL
Battery	4700mAh
Cleaver Blade	BI-07
Electrode	EI-23
External Power	DC 12V available for car cigar jack
Sleeve	S-160 (60mm), S-140 (40mm)
Sleeve Clamp	-
Sleeve Loader (2ea)	-
Optical Fiber Holder	HS-250, HS-900, HS-2.5F, HS-IN, HS-SC/FC, HS-ILC, HS-ST, LS-900(Loose tube)
SOC Connector	SC, LC, FC, ST (refer to FTTx solution catalogue)
Work Belt	-

* Design, standard/optional package and specification shown above are subject to change with or without notice.

UCLSWIFT KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509) | Tel +82 42.671.5610 | Fax +82 42.671.5612 | sales@uclswift.com

USA 4230 LBJ Freeway, Ste.149 Dallas, TX 75244, USA | (+1) 972 556 0916

INDIA Ilisintech Trading India Pvt.Ltd 621, Devika Tower, Nehru Place New Delhi 110019, India | (+91) 011 4055 5954

CHINA Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950

RUSSIA Office 401(Kotra) 4F Hotel "Korston" 15 st. Kosygina, Moscow, 119334, Russia | (+7) 985 997 7185

EUROPE Zirovnicka 2/2389 106 00 Prague 10, Czech Republic | (+420) 725 001 757

INDONESIA FACTORY Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia

