
TECHNICAL SPECIFICATION

4310F-NF 01







4.3-10 straight female to N straight female adapter

ID:2.4.81.8212.1

Rev: A0

Material and Plating

Center contact Tin-bronze / Silver Plated
Outer contact Tin-bronze / Silver Plated

Body Brass / Silver Plated

Dielectric PTFE

Gasket Silicon Rubber

Electrical Specifications

Characteristics Impedance 50 Ohm Frequency Range DC~6GHz Insulation Resistance ≥10000MΩ Dielectric Withstanding Voltage 2500V rms Operating Voltage 1400V rms Contact resistance 4.3-10 type N type Center contact resistance ≤1.5 mΩ ≤1.0mΩ ≤0.25mΩ Outer contact resistance ≤1.5 mΩ @DC-3 GHz Insertion Loss ≤0.10dB **VSWR** @DC-3 GHz ≤1.10 ≤-160dBc PIM3(2*43dBm)

Environmental & Mechanical Specifications

Durability (matings) ≥500 cycles

Mechanical Shock Test Method MIL-STD-202, Method 213, Test Condition D

Vibration Test Method MIL-STD-202, Meth. 204, Cond. A

Temperature Range -65°C to +165°C

RoHS Compliant

Regulatory Compliance / Certification

ISO 9001:2015 Compliant

The facts and figures contained herein are carefully complied to the best of our knowledge, but they are intended for general informational purposes only.

Maahantuoja / Imported by: Orbis Oy, www.orbis.fi

Tuotekoodi / Product code: 3003578