

Hybrid Combiner 95322XXX

698-3800MHz



- ◆ Wide-band design, cover 698-3800MHz
- ◆ Low PIM
- ◆ Compact size and light weight
- ◆ Easy to be installed
- ◆ Suitable for indoor and outdoor applications
- ◆ Connector Type, Twisthead



Technical Data

Electrical Specifications			Orbis code		
Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95322263	95322283	95322303
		≤-155	95322265	95322285	95322305
		≤-160	95322267	95322287 3006128	95322307
Frequency Range (MHz)			698-3800		
Insertion Loss (dB)			3±0.5		
Isolation (dB)			> 25		
VSWR (dB)			< 1.25		
Input Power (W)			<300	<300	<500
Peak Power (W)			<800	<1500	<2000
Impedance (Ω)			50		
Mechanical Specifications					
Dimensions,HxWxD(excluding connectors and mounting bracket)(mm)			133.5x42.6x29.5		
Weight (including connectors and mounting bracket) (kg)			0.48	0.5	0.7
Connector Type			N Female	4.3-10 Female	7-16 Female
Packing Size(mm)			215x140x75		
Color			Light Gray(Customizable)		
Mounting			Wall Mounted		
Environmental Specifications					
Operational Temperature (°C)			-40 to +65		
Operational Humidity (%)			≤95		
Ingress Protection Class			IP65(Indoor and Outdoor)		

